

IAP6 Rec'd PCT/PTO 25 JUL 2006

Description

RECORDING MEDIUM, REPRODUCTION DEVICE, PROGRAM, AND REPRODUCTION
METHOD

5 Technical Field

0001

The present invention relates to seamless playback, and more specifically to improvements in consumer reproduction devices and recording media which support GUI technology. Typical examples of
10 such recording media are BD-ROM (Blu-ray Disc Read Only Memory) and DVD-video.

Background Art

0002

15 Seamless playback is used when playing back a plurality of digital streams to eliminate interruptions that occur when switching from one digital stream to the next. Multi-story movies in which the plot changes in response to user operations or device status (e.g. a rating level setting) are produced using seamless playback
20 technology. There are currently many in the movie business who would like to make use of this technology to add value to their products and boost the share price of their company.

0003

Each digital stream includes a video stream constituting a
25 moving picture, an audio stream constituting sound, and elementary streams of various types, including a graphics stream constituting subtitles and menus. The above streams are multiplexed to form the digital stream. Technology that enables seamless playback of video

streams multiplexed into a plurality of digital streams is disclosed in the patent documents 1 and 2.

Patent Document 1: International publication W097/13367

Patent Document 2: International publication W097/13363

5

Disclosure of the present invention

Problems the present invention aims to solve

0004

When a movie is composed of a plurality of digital streams, each stream may be played back independently or immediately following another digital stream as part of a sequence. In conventional DVD reproduction devices, an internally provided video decoder (for decoding video stream data) makes a clear distinction between independent playback and playback immediately following another digital stream. In the latter, the conventional DVD reproduction device is able to realize seamless playback of the video stream by ensuring that the presence of data in memory in the video decoder is continuous. In an internally provided graphics decoder (for decoding graphics stream data), on the other hand, memory holding the graphics stream data is all cleared when switching from one digital stream to another. When the video streams are being played back seamlessly a given graphics stream may not be independent of the graphics stream in a preceding digital stream. However, even if the graphics streams are not independent, the graphics stored in the reproduction device will be cleared at the switch-over from one digital stream to another. As a result, momentary interruptions in the display of subtitles and menus occur at the switch-over.

0005

VIC

Owing to the momentary interruptions that occur in the display of subtitles and menus, an author must expend time and effort selecting appropriate points at which to place digital stream boundaries. The boundaries may be chosen to include scenes without any lines and other sections where no subtitles or graphics appear. Thus, when a movie is being split into a plurality of digital streams using conventional technology, there is a problem in that the author is constrained to select portions not including speech as points for placing digital stream boundaries.

10 0006

Consequently, when making multi-story type movies, it is often impossible to realize playback in accordance with the desired storyline.

15 The object of the present invention is to provide a recording medium that reduces constraints on the selection of boundaries and thereby simplifies the production of movies having a number of playback paths.

Means to solve the problem

20 0007

25 In order to achieve the above object, the recording medium of the present invention is a recording medium having recorded thereon one or more digital streams each generated by multiplexing a video stream and a graphics stream, wherein the video stream constitutes a moving picture, the graphics stream constitutes graphics to be overlaid on the moving picture, and includes status information, and if the digital stream is to be played back by a reproduction device immediately following another digital stream, the status

information indicates that presence of management data already in memory for graphics display is to be continuous.

Effects of the present invention

5 0008

According to the above construction, the status information instructs the reproduction device to continue memory management at the playback switch-over from a preceding digital stream to an immediately following digital stream. Consequently, the reproduction device does not reset the graphics decoder when playback switches between the digital streams. Having menu management continue makes it possible to select a portion at which menus or subtitles are displayed at a digital stream boundary. This reduces constraints on the selection of points for placing boundaries between digital streams, and in the case of a multi-story type movie, enables playback that follows a desired storyline.

10
15

Brief Description of the Drawings

0009

20 FIG. 1 shows a use of a recording medium of the present invention;
FIG. 2 shows an application layer format of a BD-ROM expressed using a directory structure;

FIG. 3 shows a schematic structure of an AV clip;

FIG. 4A shows a structure of a presentation graphics stream;

25 0010

FIG. 4B shows PES packets obtained by converting functional segments;

FIG. 5 shows a logical structure made up of functional segments

of various types;

FIG. 6 shows a playback time axis of an AV Clip to which a DS_n is allocated;

FIG. 7A shows a data structure of an ODS;

5 0011

FIG. 7B shows a data structure of a PDS;

FIG. 8A shows a data structure of a WDS;

FIG. 8B shows a data structure of a PCS;

FIG. 9 illustrates an example of how subtitles are realized;

10 FIG. 10 shows an example of a PCS in a DS₁;

FIG. 11 shows an example of a PCS in a DS₂;

FIG. 12 shows a playback time axis of an AV Clip to which a DS_n is allocated;

15 FIG. 13A shows an Epoch that has continuity between two AV clips;

0012

FIG. 13B shows how Display Sets of an Epoch Continue type are managed;

20 FIG. 14 shows three conditions necessary for continuity between two AV Clips;

FIG. 15 shows a screen composition for DS_m and a screen structure DS_m + 1 for comparison;

FIG. 16 shows an Epoch divided into two parts at a boundary between AV Clips;

25 FIG. 17 shows how an Epoch Continue is managed at a branch point when two AV Clips (AV Clip #2 and AV Clip #3) are available to follow a single AV Clip (AV Clip #3);

FIG. 18 shows how an Epoch Continue is managed at a point where

two preceding AV Clips (AV Clip #1 and AV Clip #4) merge to a single AV Clip (AV Clip#2);

FIG. 19 shows files having an extension "clpi" and files having an extension "mpls";

5 FIG. 20 shows a structure of a piece of PL information;

FIG. 21 shows an example of pieces of PL information in the case where two AV Clips are to be managed as a single PlayList;

FIG. 22 shows a Display Set belonging to each PlayItem (AV Clip), and the connection_condition of each PlayItem;

10 FIG. 23 shows an Epoch that contains DSm + 1 at the head of PlayItem#2 (a following AV Clip), and DSm at an end of PlayItem#1;

FIG. 24 shows an internal structure of a reproduction device of the present invention;

15 FIG. 25 is a flow chart showing a processing order for loading functional segments;

FIG. 26 shows how Display Sets are read when playing back the two AV clips shown in FIG. 14;

FIG. 27 shows how Display Sets are read to a graphics decoder when skip playback of the AV Clip #2 is carried out in order;

20 FIG. 28 shows for comparison a PTS value of a video stream belonging to the preceding AV Clip and a PTS value of a video stream belonging to the following AV Clip;

FIG. 29A shows a structure of an interactive graphics stream;
0013

25 FIG 29B shows PES packets obtained by converting functional segments;

FIG. 30 shows a logical structure made up of functional segments of various types;

FIG. 31 shows correspondences between ICSs and an interactive_composition;

FIG 32 shows a data structure of an ICS;

FIG. 33 shows a data structure of page information for a given
5 page (page y) among a plurality of pages in an x-th Display Set;

FIG. 34 shows setting for a page_version_number field in two consecutive Display Sets (DSx + 1, DSx);

FIG. 35 shows settings for the page_version_number field in two consecutive Display Sets (DSx + 1, DSx);

10 FIG. 36 shows a page composed of page information (y) in Dsx and Page information (y) in DSx + 1 for comparison;

FIG. 37 show a processing order followed by a graphics controller
17 when there is an Epoch Continue-type Display Set in an IG stream;
and

15 FIG. 38 is a flow chart showing a manufacturing process for producing a BD-ROM described in the first to third embodiments.

0014

Best Mode for Carrying Out the Present invention

20 The following describes embodiments of the recording medium of the present invention. First, applications of the recording medium of the present invention are described. FIG. 1 shows an exemplary application of the recording medium. The recording medium in FIG. 1 is a BD-ROM 100. The BD-ROM 100 is used to provide movies in a
25 home theater system that includes a reproduction device 200, a remote control 300, and television 400.

0015

An application of the recording medium of the present invention

is described above. The following describes a way of producing the recording medium. The recording medium can be produced by making improvements to a BD-ROM application layer.

FIG. 2 shows an application layer format of a BD-ROM expressed using a directory structure. As shown in FIG. 2, The BD-ROM includes a BDMV directory under a ROOT directory.

Subordinate to the ROOT directory there are four subdirectories. These are a PLAYLIST directory, a CLIPINF directory, a STREAM directory, and a BDJA directory. The STREAM directory stores a file group constituting digital streams. Each file has an extension "m2ts", and the file group includes 00001.m2ts, 00002.mts, and 00003.m2ts.

0017

The PLAYLIST directory stores a file group constituting static scenarios. Each file has an extension "mpls", and the file group includes 00001.mpls, 00002.mpls, and 00003.mpls.

The CLIPINF directory stores a file group constituting static scenarios, similarly to the PLAYLIST directory. Each file has an extension "clpi", and the file group includes 00001.clpi, 00002.clpi, and 00003.clpi.

20 0018

In FIG. 2, the files with the extension "m2ts" (00001.m2ts, 00002.mts, 00003.m2ts...) store AV Clips. The AV Clips include Main Clips and Subclips. Each Main Clip is a digital stream generated by multiplexing a plurality of elementary streams, typical examples of which include a video stream, an audio stream, a presentation graphics stream (PGstream) constituting subtitles, and an interactive graphics stream (IG stream) constituting menus.

0019

0019

FIG. 3 shows a typical structure of an AV Clip.

The AV Clip (see middle level in FIG. 3) is constructed as follows. The video stream which is made up of a plurality of video frames (pictures pj1, pj2, pj3,...) and the audio stream which is made up of a plurality of audio frames (upper level 1) are each converted to PES packets (upper level 2), and further converted to TS packets (upper level 3). Likewise, the Presentation Graphics stream (PG stream) which is made up of subtitles and the like and the Interactive Graphics stream (IG Stream) (lower level 1) are converted to PES packets (lower level 2), and subsequently converted to TS packets (lower level 3). These TS packets of the video, audio, Presentation Graphics and Interactive Graphics streams are multiplexed to generate the AV Clip.

0020

When recorded on a BD-ROM each of the TS packets included in the AV Clip is allocated an extension header. The extension header is called TP_extra_header, is 4 bytes in length, and includes an arrival_time_stamp and a copy_permission_indicator. The TS packets with attached TP_extra_headers are collected into groups each containing 32 packets, and written to 3 sectors of the BD-ROM. Each group containing the 32 packets is 6144 bytes ($= 32 \times 192$) in size, and therefore matches the 6144-byte size ($= 2048 \times 3$) of the three sectors. In combination, the three sectors storing the 32 TS packets with attached TP_extra_headers are called an "Aligned Unit".

0021

The AV clip is described above. The following describes the Presentation Graphics stream. FIG. 4A shows a structure of the Presentation Graphics stream. Level 1 shows the TS packets that make

up the AV Clip. Level 2 shows the PES packets that make up the graphic stream. Each PES packet in level 2 is formed by extracting the payloads of TS packets with a prescribed PID from the TS packets in level 1, and combining the extracted payloads.

5 0022

Level 3 shows a structure of the graphics stream. The graphics stream includes functional segments called a PCS (Presentation Composition Segment), a WDS (Window Definition Segment), PDS (Palette Definition Segment), an ODS (Object Definition Segment), and an END (END of Display Set Segment). Of these functional segments, the PCS is a screen composition segment, and the WDS, PDS, ODS and END are definition segments. The PES packets are in one-to-one correspondence with the functional segments. Each functional segment is either converted to a single PES packet and recorded on the BD-ROM or fragmented, converted to a plurality of PES packets and recorded on the BD-ROM.

0023

FIG. 4B shows PES packets obtained by converting functional segments. As shown in FIG. 4B, the PES packets are composed of "packet headers" and "payload", where the payload is the functional segment. Besides the payload, each packet has a corresponding DTS and PTS. Hereinafter, the DTS and PTS in the header of the PES packet that contains the functional segment are regarded as the DTS and PTS of that functional segment.

0024

25 These functional segments of various types make up a logical structure of the type shown in FIG. 5. In FIG. 5, level 3 shows functional segments, level 2 shows Display Sets, and level 1 shows Epochs. Each Display Set (abbreviated to DS) in level 2 is a string of functional

segments, from the functional segments that make up the graphics stream, that together make up a single screen of graphics. In FIG. 5, broken lines kzl indicate which DS the functional segments belong to. It is clear from the figure that the string of functional segments denoted by PCS-WDS-PDS-ODS-END compose one DS. The reproduction device reads the plurality of functional segments that compose the single DS to produce one screen of graphics.

0025

Each Epoch in level 1 is a time period, on the playback time axis of the AV Clip, over which memory management is continuous, and a group of data allocated to that time unit. The memory to be managed includes a Graphics Plane for storing one screen of Graphics and an Object Buffer for storing uncompressed graphics data. Saying that memory management is continuous over the Epoch means that (i) neither the Graphics Plane nor Object Buffer is flushed during the Epoch (where to flush means to clear the entire Graphics Plane or the Entire Object Buffer), and (ii) deletion and rendering of graphics are performed only within a predetermined rectangular area of the Graphics Plane during the Epoch. In other words the rectangular area is fixed in size and position over the Epoch. When deletion and rendering of graphics is confined to the fixed rectangular area, synchronization of graphics and video is guaranteed. In other words, the Epoch is a time unit on the playback time axis during which the synchronization of video and graphics is guaranteed. To change the predetermined area for which rendering/deletion is performed, it is necessary to define a change point on the playback time axis and set a new Epoch from that point forward. In this case, synchronization of video and graphics is not guaranteed at the boundary between the two epochs.

0026

With regard to subtitling, a time period on the reproduction time axis during which subtitles appear within a fixed rectangular area can be a single Epoch. FIG. 6 shows the relationship between subtitle display positions and Epochs, and may be considered to show a situation in which subtitle display positions are changed depending on picture form. Of the four subtitles, which are "Honestly", "I'm sorry", "That happened" "three years ago", two are positioned at the top of the screen and two at the bottom. More specifically, "Honestly" and "I'm sorry" are at the bottom and "That happened" and "three years ago" are at the top. The subtitle display positions are altered so as to correspond with empty regions of the screen in order to make the subtitles easier to see. In this case, the time period on the AVClip time playback time axis during which the subtitles are displayed at the bottom of the screen is Epoch1, and the time period during which the subtitles are displayed at the top of the screen is Epoch 2. Thus, each of the two Epochs has a separate subtitle rendering area. In Epoch 1, the subtitle rendering area (Window 1) is in the bottom margin of the screen. In Epoch 2 the subtitle rendering area (Window 2) is in the top margin of the screen. In each of Epoch 1 and Epoch 2 continuous memory management of the Graphics Plane and buffer is guaranteed, so the subtitles are displayed seamlessly in the corresponding margin. This completes the description of the Epoch. The following describes a Display Set.

25 0027

In FIG. 5 broken lines hk1 and hk2 indicate an Epoch, in level 1, that contains the Display Sets in level 2. As is clear from FIG. 5, a series of DS, including an Epoch Start DS, an Acquisition Point

DS, and a Normal Case DS, constitute the Epoch. Note that the Epoch Start DS, Acquisition Point DS, and Normal Case DS denote types of DS. Though the Acquisition Point DS precedes the Normal Case DS in FIG. 5, this is merely an example and the order may be reversed.

5 0028

The Epoch Start DS indicates the beginning of a new Epoch. Thus, the Epoch Start DS contains all the functional segments necessary for a next screen composition. The Epoch Start DS is provided at a position likely to be chosen as a starting point, such as the beginning
10 of a section in a movie.

The Acquisition Point DS is not an Epoch starting point, but contains all functional segments necessary for a next screen composition. As a result, graphics can be displayed reliably if playback is started from the Acquisition Point DS. In other words,
15 the Acquisition Point DS enables screen composition from a midpoint in the Epoch.

The Acquisition Point DS is provided at a position that may be chosen as a starting point, such as a position that is specifiable using a time search. "Time search" is to an operation by which a
20 user inputs a number of minutes/seconds to locate a playback point. If the input units are, say, 10 seconds (or 10 minutes), corresponding playback points positioned at intervals of 10 seconds (or 10 minutes), will be specifiable using the time search. If the Acquisition Point DSs are provided in positions that are specifiable using the time
25 search, the graphics stream can be played back satisfactorily when the time search is performed.

0029

The Normal Case DS contains only difference data relative to

the previous Display Set. For example, if a DSv has the same subtitles as an immediately preceding Dsu but has a different screen composition from the DSu, the DSv will be a Normal Case DS containing only a PCS and an END. With this arrangement, there is no need to provide ODSs that have already been provided. As a result, the amount of data stored on the BD-ROM can be reduced. On the other hand, it is not possible to display graphics using only the Normal Case DS containing difference data.

0030

10 The following describes the Definition Segments (ODS, WDS, and PDS).

 The Object_Definition_Segment is a functional segment for defining a graphics Object. The following describes this graphics Object. AV Clips recorded on BD-ROMs feature an image quality equivalent to that of high-definition television pictures. The resolution for displaying graphics Objects is set to an equivalently high 1920 × 1080. This high resolution permits reproduction of movie theater style subtitles (e.g. crisp handwriting style subtitles) using BD-ROMs. A graphics Object is made up of plurality of pieces of run-length data. Run-length data expresses a Pixel String using a Pixel Code that indicates a pixel value and a continuous length of the pixel value. The Pixel Code is 8 bits in length, and takes a value of 1 to 255. The Run-length data is able to select 256 colors of a possible 16,777,216 in accordance with the Pixel Code, and set the pixel color. Note that when a graphics Object is a subtitle, it is necessary to dispose a character string on a transparent background.

0031

2000 100

The ODS defines a graphics Object according to a data structure shown in FIG. 7A. As shown in FIG. 7A, the ODS is composed of a segment_type field indicating that the segment is of the ODS type, a segment_length field indicating a data length of the ODS, an object_id field uniquely identifying the graphics Object in the Epoch, an object_version_number field indicating a version of the ODS in the Epoch, a last_in_sequence_flag field, and an object_data_fragment field containing a consecutive sequence of bytes corresponding to part or all of the graphics Object.

10 0032

The Palette Definition Segment (PDS) is a functional segment for storing palette data. The palette data indicates combinations of Pixel Codes of 1 to 255 and pixel values. Each pixel value is composed of a red difference component (Cr value), a blue difference component (Cb value), a luminance component (Y value), and a transparency (T value). Each pixel code in the run length data is exchanged for a pixel value indicated by the palette to generate a color. The data structure of PDS is shown in FIG. 7B. As shown in FIG. 7B, the PDS includes a segment_type field indicating that the segment is of the PDS type, a segment_length field indicating a data length of the PDS, a palette_id field for uniquely identifying the palette included in the PDS, a palette_version_number field indicating a version of the PDS within the epoch, and a palette_entry field carrying information for each entry. The palette_entry field indicates a red difference component (Cr_value), a blue difference color component (Cb_value), a luminance component (Y_value), and a transparency (T_value) for each entry.

0033

The following describes the WDS.

The window_definition_segment is a function segment that defines a rectangular area on the Graphics Plane. As described above, continuous memory management over an Epoch is only possible if clearing and rendering are limited to a fixed rectangular area on the Graphics Plane. The rectangular area on the Graphics Plane is called a "Window", and is defined by WDS. FIG. 8A shows the data structure of the WDS. As shown in FIG. 8A, the WDS is expressed using a window_id field uniquely identifying the Window on the Graphics Plane, a window_horizontal_position field indicating the horizontal position of a top left pixel on the Graphics Plane, and a window_vertical_position field indicating a vertical position of a top left pixel on the Graphics Plane, a window_width field indicating a width of the Window on the Graphics Plane, and a window_height field indicating a height of the Window on the Graphics Plane.

0034

The window_horizontal_position field, the window_vertical_position field, the window_width field, and the window_height field can contain the following values. The Graphics Plane serves as a coordinate system for these field values. This Graphics Plane has a two-dimensional size defined by video_height and video_width parameters.

The window_horizontal_position field specifies a horizontal position of the top left pixel of the Window on the Graphics Plane, and thus takes value in a range of 1 to the video_width. The window_vertical_position field specifies the vertical position of the top left pixel of the Window on the Graphics Plane, and thus takes a value in a range of 1 to the video_height.

0035

The `window_width` field specifies the width of the Window on the Graphics Plane, and thus takes a value in a range of 1 to $(\text{video_width}) - (\text{window_horizontal_position})$. The `window_height` field specifies the height of the Window on the Graphics Plane, and thus takes a value in a range of 1 to $(\text{video_height}) - (\text{window_vertical_position})$.

A position and size of a Window can be defined for each Epoch using the `window_horizontal_position`, `window_vertical_position`, `window_width`, and `window_height` fields in the WDS. The author is therefore able to make adjustments to a Window at time of authoring to ensure that there is no interference with elements of the picture over the period of an Epoch. For instance, the Window may be made to appear in a desired margin. Subtitles displayed using graphics can be clearly viewed. Moreover, since it is possible to define a WDS for each epoch, the graphics can be moved as elements of the picture change with time. This enables a clear view of the graphics to be maintained. As a result, the quality of the movie product can be raised to the level of a cinema film, in which subtitles are integrated into the picture.

0036

The following describes an END of Display Set Segment. The END of Display Set Segment is a functional segment indicating that transmission of a Display Set is complete, and is positioned immediately after the last ODS in the Display Set. The END of Display Set Segment includes a `segment_type` field indicating that the segment is of the END of Display Set type, and a `segment_length` field indicating a data length of the END of Display Set Segment. The END of Display

Set Segment is not a main feature of the present invention. Thus, further description of the END of Display Set Segment is omitted.

0037

The ODS, PDS, WDS and END are described above. The following
5 describes the PCS.

The PCS is a functional segment for constituting an interactive screen. FIG. 8B shows a data structure of the PCS. As shown in FIG. 8B, the PCS includes a segment_type field, a segment_length field, a composition_number field, a composition_state field, a
10 palette_update field, a palette_id_ref field, and composition_object fields (1) to (m).

0038

The composition_number field identifies a graphics update in the Display Set, using a number from 0 to 15. Specifically, the
15 composition_number field is incremented by one for each graphics update from the beginning of the Epoch to the PCS containing the composition_number field.

The composition_state field indicates whether the Display Set starting from the PCS is a Normal Case-type Display Set, an Acquisition
20 Point-type Display Set, or an Epoch Start-type Display Set.

0039

The palette_update_flag field indicates whether the PCS describes a Palette-only Display Update. The Palette-only Display Update is an update that is limited to replacing the palette with
25 a new palette. To indicate a Palette-only Display Update, the palette_update_flag is set to 1.

The palette_id indicates whether the PCS describes a Palette-only Display Update. The Palette-only Display Update is an

update that is limited to replacing the palette with a new palette. To indicate a Palette-only Display Update, the `palette_update_flag` is set to 1.

0040

5 The `composition_object` fields (1) to (m) each contain control information for realizing a screen composition using the Display Set to which the PCS belongs. In FIG. 8b, a `composition_object(i)` is expanded, as indicated by broken lines wdl, to illustrate an internal structure of the `composition_object` fields. As illustrated, the
10 `composition object(i)` includes an `object_id_ref`, a `window_id_ref`, an `object_cropped_flag`, an `object_horizontal_postion`, an `object_vertical_position`, and `cropping_rectangle_information(1)` to `cropping_rectangle_information(n)`.

0041

15 The `object_id_ref` field contains a reference value that is an `object_id` associated with a graphics Object. This reference value identifies the graphics Object that is to be used to produce a section of the screen composition corresponding to the `composition_object(i)`.

 The `window_id_ref` field contains a reference value that is
20 a Window identifier (`window_id`). This reference value specifies the Window in which the graphics Object is to be displayed in order to produce the section of the screen composition corresponding to the `composition_object(i)`.

0042

25 The `object_cropped_flag` field indicates whether or not a graphics Object cropped in the Object Buffer is to be displayed. When the `object_cropped_flag` field is set to 1, the cropped graphics Object in the Object Buffer is displayed. When the `object_cropped_flag`

field is set to 0, the cropped graphics Object in the Object Buffer is not displayed.

0043

The object_horizontal_position field specifies a horizontal position of a top left pixel of the graphics Object on the Graphics Plane.

The object_vertical_position field specifies a vertical position of a top left pixel of the graphics Object on the Graphics Plane.

The cropping_rectangle information(1) to cropping rectangle information (n) fields are valid when the object_cropped_flag field is 1. The cropping_rectangle information(i) is expanded, as indicated by broken lines wd2, to illustrate an internal structure of the composition_rectangle information. As illustrated, the cropping_rectangle information(i) includes an object_cropping_horizontal position field, an object_cropping_vertical position field, and object_cropping_width field, and an object_cropping_height field.

0044

The object_cropping_horizontal position field specifies a horizontal position of a top left corner pixel of a cropping rectangle in the graphics Object. The cropping rectangle is used to remove a portion of the graphics Object, and corresponds to a "region" in the ESTI EN 300 743 standard.

The object_cropping_vertical position field specifies a vertical position of the top left corner pixel of the cropping rectangle on the Graphics Object.

0045

The `object_cropping_width` field specifies a width of the cropping rectangle in the Graphics Object.

The `object_cropping_height` field specifies a height of the cropping rectangle in the Graphics Object.

5 The data structure of the PCS is described above. The following describes a specific example of the PCS. In the example, the subtitles "Honestly" and "I'm sorry" shown in FIG. 6 are displayed in sequence by writing to the graphics plane three times as the moving picture is reproduced. FIG. 9 illustrates how the subtitles are realized.

10 In FIG. 9, an Epoch includes DS1 (Epoch Start) and DS2 (Normal Case). The DS1 includes a WDS defining a window in which the subtitles are to be displayed, an ODS including the line "Honestly, I'm sorry", and a first PCS. The DS2 includes a second PCS.

0046

15 The following describes each PCS. FIGs. 10 to 12 show examples of the WDS and PCS. FIG. 10 shows the PCS in DS1.

 In FIG. 10, a `window_horizontal_position` field value and a `window_vertical` field value in the WDS specify top left coordinates LP1 of the Window on the Graphics Plane, and a `window_width` field value and a `window_height` field value in the WDS specify a height and width of the Window.

20

0047

 In FIG. 10, an `object_cropping_horizontal_position` field value and a `window_vertical_position` field value specify a basepoint ST1 of a cropping rectangle in a coordinate system whose origin is the top left of the of the Graphics Object in the Object Buffer. The cropping rectangle (enclosed by a thick line) is then defined using an `object_cropping_height` field value, an `object_cropping_width`

25

field value and the basepoint ST1. The cropped graphics Object is then disposed in a region cpl (enclosed by a broken line) so that a top left corner of the cropped Graphics Object lies at a pixel specified by an object_horizontal_position field value and an object_vertical position field value in the coordinate system of the Graphics Plane. This causes "Honestly" to be written into the window of the graphics plane. Consequently, the subtitle "Honestly" is displayed in combination with the moving picture.

0048

FIG. 11 shows the PCS in DS2. Since the WDS in FIG. 11 is the same as that of FIG. 10 its description is omitted. The cropping rectangle in FIG. 11, however, differs from that of FIG. 10. An object_cropping_horizontal_position and an object_cropping_vertical_position specify top left coordinates of a cropping rectangle corresponding to "I'm sorry" from the line "Honestly I'm sorry", and the object_cropping_height and object_cropping_width specify a height and width of the cropping rectangle corresponding to "I'm sorry". This causes "I'm sorry" to be written into the Window on the Graphics Plane. Consequently, the subtitle "I'm sorry" is displayed in combination with the moving picture.

0049

The functional segments are described above. The following describes the manner in which Display Sets including PCSs and ODSs are allocated to the playback time axis of the AV Clip. An Epoch is a period on the playback time axis over which memory management is continuous, and each Epoch constitutes one or more Display Sets. At issue, therefore, is the manner in which the one or more Display

Sets are allocated to the playback time axis. Note that the playback time axis is an assumed axis used to prescribe decoded timings and playback timings for each frame of picture data making up the video stream that is multiplexed into the AV Clip. The decode timing and playback timing are expressed to an accuracy of $1/90000$ seconds. The DTS and PTS associated with the PCS and ODS in the Display Set specify timings for synchronous control on the playback time axis. In other words, the DSs are allocated to the playback time axis by carrying out synchronous control using the DTSSs and PTSSs associated with the PCSs and ODSs.

0050

A Display Set DS_n of the Display Sets belonging to the Epoch is allocated to the playback time axis using a PTS and DTS which are set as shown in FIG. 12. FIG. 12 shows the AV Clip playback time axis to which the DS_n has been allocated. In FIG. 12, the start of the DS_n period is specified by a DTS value ($DTS(DS_n[PCS])$) of a PCS belonging to the DS_n , and the end of the period is specified by a PTS value ($PTS(DS_n[PCS])$) of the same PCS. The timing for the first display is also specified by the PTS value ($PTS(DS_n[PCS])$) if the PCS. If the timing of a desired picture in a video stream is matched with the $PTS(DS_n[PCS])$, first display of the DS_n will synchronize with the video stream.

0051

The $PTS(DS_n[PCS])$ is a value obtained by adding $DTS(DS_n[PCS])$ a period for decoding ODS ($DECODEDURATION$) to the $DTS(DS_n[PCS])$.

Decoding necessary for the first display of the DS_n is performed in the $DECODEDURATION$. In FIG. 12, a period mcl is a period during which an arbitrary ODS(ODS_m) belonging to the DS_n is decoded. The

starting point of the decode period mcl is specified by $DTS(ODSn[ODSm])$, and the end point of the decode period mcl is specified by $PTS(ODSn[ODSm])$.

0052

5 The Epoch is therefore prescribed by allocating each of the ODSs in the Epoch to the playback time axis. The above describes the allocation to the playback time axis.

 The Epoch is a unit over which memory management in the graphics decoder is continuous. Thus, it is normally necessary that the Epochs
10 finish within a single AV Clip. However, when two AV Clips are played back in sequence and three prescribed conditions are met, it is possible to define an Epoch that is continuous over the boundary between the AV Clips.

0053

15 FIG. 13A shows an Epoch that is continuous across a boundary between two AV Clips. Level 1 in FIG. 13A shows the two AV Clips that are to be played back consecutively. Level 2 shows an Epoch that is continuous across a boundary between the two AV Clips. Level 3 shows the Display Sets that belongs to the Epoch in level 2. The
20 Epoch shown in level 2 is not divided at the boundary between AV Clips. In the Display Sets in level 3, however, there is a boundary between the Display Sets at the boundary between the AV Clips. Note that in FIG. 13A the Display Set ($DSm + 1$) positioned immediately after the boundary between the AV Clips is of an Epoch Continue type.

25 0054

 Epoch Continue refers to the type of the Display Set ($DSm + 1$) positioned immediately after the boundary between the AV Clips. The Display Set ($DSm + 1$) is treated as an Acquisition Point if the

three prescribed conditions are met, and an Epoch Start if one or more of the three conditions is not met.

FIG. 13B shows the manner in which display a Display Set of the Epoch Continue type is treated. As is clear from FIG. 13B, the Display Set of the Epoch Continue type is treated as an Epoch Start in the case of skip playback from a subsequent AV clip, and as an Acquisition Point in the case of consecutive playback from the immediately preceding AV Clip.

0055

FIG. 14 shows the conditions for ensuring continuity between the two AV Clips. Level 1 in FIG. 14 shows two AV Clips that are to be played back consecutively and level 2 shows three Epochs. Of these three Epochs, the middle Epoch is the one in which memory management is continuous across the boundary between the two AV Clips. Level 3 shows Display Sets that belong to respective Epochs. The Epochs in level 2 have boundaries that differ in position from the boundaries of the AV Clips. Level 4 shows the functional segments that belong to each Display Set. The group of functional segments in level 4 is the same as that in level 4 of FIG. 5. The symbols double circle 1, double circle 2, and double circle 3 in FIG. 14 indicate the conditions for establishing an Epoch with continuity across the boundary between the two AV Clips. The first condition is that the Display Set ($DS_m + 1$) positioned immediately after an AV Clip Boundary is of the Epoch Continue type.

0056

The second condition is that a composition_number in a PCS belonging to the $DS_m + 1$ is identical to a composition_number (= A) in a PCS belonging to the DS_m , which immediately precedes the

DSm + 1 (i.e. the content of the graphics is the same before and after the boundary between the two AV clips). The composition_number refers to a screen composition that uses the Display Set. Thus, if the composition_numbers in the DSm and DSm + 1 are equal, the graphics
5 obtained using screen compositions corresponding to these Display Sets are the same. FIG. 15 shows the screen composition of DSm and the screen composition of DSm + 1 for comparison. As shown in FIG. 15, the graphics corresponding to the DSm are "three years ago", and the graphics corresponding to the DSm + 1 are also "three years
10 ago". Thus, the graphics produced by the two display sets are identical, and it is clear that the Composition_numbers will be identical. Also, since the video streams are played back seamlessly, the DSm + 1, it is clear that the DSm + 1 will be treated as an acquisition point.

0057

15 The third condition is that playback of the AV Clip and the immediately following AV Clip is seamless. Seamless playback of the video stream is conditional upon the following.

(i) The display method (e.g. NTSC, PAL) for the video stream, which is specified by attribute information, is the same in both
20 AV Clips.

0058

(ii) The encoding method (e.g. NTSC and PAL) for the audio stream, which is specified by the attribute information, is the same in both AV Clips.

25 If, in (i) and (ii), the display methods and encoding methods for the video and audio streams are different, seamless playback cannot be performed because the video decoder and audio decoder stop operating momentarily in order to switch to a new display format,

encoding mode and bit rate.

0059

For example, when two audio streams are to be played back consecutively and one is encoded using the AC-3 method and the other using an MPEG standard, the audio decoder stops decoding momentarily
5 between the two streams in order to carry out an internal switch of attributes. The case when the video streams are different is similar.

Seamless playback, therefore, only takes place when the conditions of (i) and (ii) are satisfied. If any of the above conditions
10 is not satisfied, seamless playback is not permitted.

0060

If the three conditions are met, the $DS_m + 1$, which is of the Epoch Continue type, is treated as an Acquisition Point. In other words, the Display Sets 1 to m and the Display Sets m + 1 to n form
15 a single Epoch, and the state of the buffer in the Graphics decoder is maintained when two AV clips are played back consecutively.

Note that, even if the $DS_m + 1$ is of the Epoch Continue type, in the case that one or both of the remaining conditions are unsatisfied, the Epoch will be divided at the boundary between the AV Clips. From
20 the above it is clear that the Display Set of the Epoch Continue type is only treated as an Acquisition Point if the three conditions are satisfied. If any one or more of the conditions is not satisfied, the Display Set of the Epoch Continue type is treated as an Epoch Start. FIG. 17 shows the manner in which an Epoch Continue type Display
25 Set is managed when there are two preceding AV Clips (AV Clip#2 and AV Clip#3) for a given AV Clip (AV Clip#1). Of the two types of preceding AV Clip, AV Clip#1 is of the type shown in FIG. 14. The AV Clip#2 that is to follow the AV Clip#1 is also of the type shown in FIG.

14. The AV Clip#1 and the AV Clip #2 therefore satisfy all three of the conditions. Thus, when played back after AV Clip#1, the first DS ($DS_m + 1$) in AV Clip#2 is treated as an Epoch Continue. The other following AV Clip, which is the AV Clip#3, has exactly the same graphic content as the AV Clip#2. Also, the composition_number in the last DS (DS_n) of AV Clip#1 matches the composition_number in the first AV Clip#3. Therefore, when AV Clip#3 follows AV Clip#1, all three conditions are satisfied, and the Epoch Continue type Display Set is treated as an Acquisition point.

10 0061

FIG. 18 shows how an Epoch Continue is managed at a merge point when two preceding AV Clips (AV Clip #1 and AV Clip #4) merge to a single AV Clip (AV Clip#2). Both AV Clip#1 and AV Clip#2 are of the type shown in FIG. 14, and satisfy the three conditions. Thus, in the case that AV Clip#1 is played back first, the first DS (DS_1) in AV Clip2 will be treated as an Epoch Continue. The AV Clip#4 has exactly the same graphic content as the AV Clip#1. Also, the composition_number in the in the last DS (DS_m) of AV Clip#4 matches the composition_number in the first DS (DS_1) of the AV Clip#2. Thus, in the case that the order of playback is AV Clip#4 to AV Clip#2, the three conditions are satisfied, and the Epoch Continue type Display Set is treated as an Acquisition Point.

0062

The above describes the AV Clip. The following describes files having the file extensions "clpi" and "mpls". FIG. 19 shows files having the extension "clpi" and files having the extension "mpls".

The files having the file extensions (0001.cpli, 0002.cpli, 0003.cpli...) are pieces of management information in one to one

correspondence with the AV clips. The pieces of management information include information such as coding format of the AV Clips in the stream, a frame rate, a bit rate, and a resolution. Each piece of management information also has an EP_Map and an ATC_Delta for indicating the head position of a GOP. The ATC (Arrival Time Clock) in ATC_Delta refers to a clock signal used as a reference for the ATC. The ATC_Delta indicates the difference between the ATC of the preceding AV Clip and the ATC of the following ATC Clip.

0063

The files having the extension "mpls" (0001.mpls, 0002.mpls, 0003.mpls...) store pieces of PL information. Each piece of PL information defines a playlist by reference to the AV Clips. FIG. 20 shows a composition of PL information. As shown on the left side of FIG. 19, marked by mp1, each piece of PL information is composed of a plurality of pieces of PlayItem information each denoted as (PlayItem()). The PlayItem is a playback section defined by specifying an in_time and an out_time on one or more AV Clip time axes. A Playlist (PL) composed of a plurality of playback sections is then defined by providing a plurality of pieces of Play Item information. The broken lines marked mp2 in FIG. 20 point indicate a close up of a composition of one piece of PlayItem information. As shown in FIG. 20, each piece of PlayItem information is composed of a clip_information_file_name field, an in_time field, an out_time field, and a connection_condition field.

0064

Settings in a piece of PL information when two AV Clips are treated as a single Playlist are described with reference to FIG. 21. Level 1 in FIG. 21 shows the two AV Clips of FIG. 15. Level 2

in FIG. 21 shows the PlayList playback time axis defined by the corresponding piece of PL information. The piece of PL information includes two pieces of PlayItem information (PlayItem#1 and PlayItem#2). The preceding AV Clip and following AV Clip are treated
5 as a single PlayList if the in_time field and the out_time field of PlayItem#1 indicate the start point and the endpoint of the preceding AV Clip and the in_time field and the out_time field of PlayItem#2 indicate the start point and the end point of the following AV Clip. Level 2 in FIG. 21 shows a playback time axis (PL Playback Time Axis)
10 of the PlayList defined by the piece of PL information. When the PlayList is defined in this way, the AV Clip is treated, in a sense, as a section of the PlayList. Each section of the PlayList is called a PlayItem. In other words, the relationship $\text{PlayItem} = \text{AV Clips}$ holds true.

15 0065

In the piece of PlayItem information that defines a PlayItem, there is a connection_condition field, which indicates whether or not whether playback of the corresponding PlayItem is to seamlessly follow playback of the preceding PlayItem (AV Clip).

20 FIG. 22 shows Display Sets belonging to each PlayItem (AV Clip), and the connection_condition field of each PlayItem. In FIG. 22, if the Display Set (DSm + 1) at the head of PlayItem#2 is of the Epoch Continue type, and the connection_condition field in the PlayItem#2 indicates a seamless connection, the DSm + 1 at the head
25 of the PlayItem#2 (the following AV Clip) and the DSm at the end of the PlayItem#1 (the preceding AV Clip) belong to a same Epoch. FIG. 23 shows the Epoch containing the DSm + 1 at the head of the PlayItem#2 (the following AV Clip) and the DSm at the end of the

PlayItem#1 (the preceding AV Clip). Since the last Display Set in the preceding AV Clip and the first Display Set of the following AV Clip belong to the same Epoch, the graphics display resulting from these two Display Sets will be continuous.

5 0066

 The above-described data structures of the Display Sets (PCS, WDS, PDS, and ODS) are instances of class structures described in programming language. A producer authoring a BD-ROM is able to obtain such data structures on the BD-ROM by describing a desired class
10 structure using syntax stipulated by a Blu-ray Disc Read Only Format. The above describes the recording medium of the embodiments of the present invention. The following describes the reproduction device of the embodiments of the present invention. FIG. 24 shows an internal structure of the reproduction device of the present invention. The
15 reproduction device of the present invention is commercially produced with an internal structure based on that shown in FIG. 24. The reproduction device of the present invention is mainly composed of three parts, these being system LSI, a drive device, and a microcomputer system, and can be commercially produced by equipping a base and
20 cabinet with these parts. The system LSI is an integrated circuit including various processing units each with a reproduction device-related function. Reproduction devices produced in this way are constructed from a BD drive 1, and arrival time clock counter 2a, a source de-packetizer 2b, a PID filter 3, Transport Buffers
25 4a, 4b and 4c, surrounding circuitry 4d, a video decoder 5, a video plane 6, an audio decoder 7, a graphics plane 8, a CLUT unit 9, an adder 10, a graphics decoder 12, a coded data Buffer 13, a surrounding circuitry 13a, a stream graphics processor 14, an object buffer 15,

a composition buffer 16, and a graphics controller 17.

0067

The BD-ROM drive 1 loads/ejects BD-ROMs, accesses a loaded BD-ROM, and from the loaded BD-ROM, reads an aligned unit composed
5 of 32 sectors.

The arrival time clock counter 2a generates an arrival time clock based on a 27 MHz liquid crystal oscillator. An Arrival Time Clock is a clock signal providing a time axis used as a reference for the ATS attached to the TS packets.

10 0068

When the Aligned Unit composed of the 32 sectors is read from the BD-ROM, the source de-packetizer 2b extracts a TP_extra_header from each of the TS packets that constitute the Aligned Unit, and outputs the stripped TS packets to the PID filter 3. Output of each
15 stripped TS packet to the PID filter 3 takes place when the time measured by the arrival time clock counter 2a reaches the ATS indicated by the corresponding TP_extra_header. Since the output to the PID filter 3 is made at the timing indicated by the ATS, the TS packets are output to the PID filter 3 in accordance with the time measured
20 by the arrival time clock, even in the case where the speed of reading from the BD-ROM varies between, for instance, a 1× speed and a 2× speed.

When two AV Clips are to be played back so that one immediately follows the other, the source depacketizer 2b corrects variation
25 between the ATC of each of the AV Clips using the ATC_Delta present in the Clip information.

0069

The PID filter 3 judges whether a TS packet belongs to the

video stream, the PG stream, or the IG stream by referring to the attached PID, and outputs to one of the transport buffers 4a, 4b or 4c accordingly.

5 The transport buffers 4a, 4b and 4c are memories which store the TS packets outputted from the PID filter 3 on a first-in first-out basis.

0070

10 The surrounding circuitry 4d contains wire logic circuitry for performing processing to convert TS packets read from the transport buffers 4a, 4b and 4c into functional segments. The functional segments obtained from the conversion are stored in the coded data buffer 13.

15 The video decoder 5 decodes the plurality of TS packets outputted from the PID filter 3 to obtain a picture in an uncompressed format and writes the picture to the video plane 6.

0071

The video plane is a plane memory used when presenting moving picture data.

20 The audio decoder 7 decodes the TS packets outputted from the PID filter, and outputs the audio data in an uncompressed format.

The graphics plane 8 is a plane memory having an area large enough for one screen, and is capable of storing the uncompressed graphics data for the one screen.

0072

25 The CLUT unit 9 converts index colors in the uncompressed data stored in the graphics plane 8 based on values of Y, Cr, and Cb indicated by the PDS.

The adding device 10 obtains an overlaid picture by multiplying

uncompressed graphics converted by the CLUT unit 9 by a T value (degree of transparency), and adding the result, pixel by pixel, to the uncompressed picture data stored in the video plane 6.

0073

5 The graphics decoder 12 decodes the graphics stream, obtains the uncompressed graphics, and writes the result to the graphics plane 8 as an uncompressed graphics object. Subtitles and menus appear as a result of decoding the graphics stream.

 The graphics decoder 12 is constructed from the coded data
10 buffer 13, the surrounding circuitry 13a, the stream graphics processor 14, the object buffer 15, the composition buffer 16, and the graphics controller 17.

0074

 The coded data buffer 13 is a buffer in which the functional
15 segments are stored together with the DTSSs and PTSSs. The functional segments are obtained by removing the TS packet headers and PES packet headers from each TS packet in the transport streams stored in the Transport buffers 4a, 4b and 4c, and sequentially arranging the resulting payloads. The PTSSs/DTSSs from the removed TS packet headers
20 and PES packet headers are stored in correspondence with the PES packets.

0075

 The surrounding circuitry 13a is wire logic for transmitting data back and forth between the coded data buffer 13 and the graphic
25 stream processor 14, and between the coded data buffer 13 and the composition buffer 16. In the processing to realize the transmission, if the current playback time reaches a time indicated in the DTS of the ODS, the surrounding circuitry 13a transmits the ODS from

the coded data buffer 13 to the stream graphics processor 14. Also, if the current playback time reaches a time indicated in the DTS of the PDS or PCS, the surrounding circuitry 13a transmits the PCS or PDS to the composition buffer 16.

5 0076

The stream graphics processor 14 decodes the ODS and writes the uncompressed graphics, which are composed of the indexed colors obtained by decoding, to the object buffer 15 as a graphics object. The stream graphics processor 14 performs the decoding instantaneously, and temporarily stores the resulting graphics object. Although the decoding by the stream graphics processor 14 is instantaneous, the writing from the stream graphics processor to the object buffer is not completed instantaneously. In a player that complies with the BD-ROM standard, the stream graphics processor 14 writes to the object buffer 15 at a transmission rate of 128 Mbps. Since the PTS in the END segment indicates when the writing to the object buffer 15 finishes, the stream graphics processor waits until the timing indicated by the PTS in the END segment before processing a subsequent DS. The graphics processor 14 starts writing the graphics object obtained by decoding an ODS 15 at a time point indicated by the DTS associated with the ODS and completes writing by the decode completion time indicated in the PTS associated with the ODS.

0077

0077

The object buffer 15 is a buffer for holding the graphics object decoded by the graphics stream processor. The object buffer 15 must be twice or four times as large as the graphics plane 8. This is to allow scrolling which requires the graphics plane to store a graphics object twice or four times as large as the graphics plane 8.

0078

The composition buffer 16 is memory for holding the PCS and PDS. In the case that there are two Display Sets to be processed, and an active period of the respective PCSs overlaps, the composition
5 buffer 16a stores a plurality of PCSs.

The graphics controller 17 interprets the PCS. Then, in accordance with the result of this interpretation, the graphical controller 17 writes the graphics object to the object buffer 15, reads the graphics object from the object buffer 15 and executes
10 display of the graphics Object. This takes place at the timing indicated by the PTS for PES packets stored in the PCSs. The interval between display, by the graphics controller 17, of a graphics Object belonging to DS_n and of a graphics Object belonging to DS_n + 1 is the interval described above.

15 0079

FIG. 25 is a flow chart showing a processing order for loading functional segments. In the flow chart SegmentK is a variable that refers to each of the Segments (ICS, PDS and ODS) as they are read during playback of the AV Clip. A disregard flag indicates whether
20 to load or disregard a given SegmentK. The flow chart is structured to include an initialization of the disregard flag to 0 (Step 1), and a loop structure for applying the processing of Steps S2 to S13 to each of the Segments (Steps S14 and S15).

0080

25 The processing of the loop structure (Steps S2 to S15) is repeated for as long as reading of functional segments continues and includes the following. First, it is judged whether the disregard flag is 0 or 1 (Step S3). If the disregard flag is 0, the target functional

segment is transmitted from the coded data buffer 13 to either the composition buffer 16 or to the stream graphics processor 14 (Step S4). If the disregard flag is 1, no transmission takes place. Instead, the target functional segment is deleted from the coded data buffer 13 (Step S5).

0081

Whether the SegmentK is loaded or disregarded is decided on the basis of the disregard flag setting. Steps S9 and S10 are processing steps for setting the disregard flag.

10 Step S6 is for judging whether or not composition_state in a PCS indicates Epoch Continue. If SegmentK is of the Epoch Continue type, Steps S7 to S9 are executed. If SegmentK is of the Normal Case type, Steps S10 to S12 are executed.

0082

15 Note that in Steps S7 to S9 judgments are made in both Step S7 and Step S8, and the disregard flag is set to 1 (Step S9) only if both of these judgments are in the affirmative.

Step 7 is for judging whether the connection_condition field of the PlayItem to which the PCS belongs is set to 5 (indicating seamless connection). Step 8 is for judging whether the composition_number in a newly read PCS is the same as the composition_number held in the composition buffer 16.

0083

25 If the either of the judgments in Steps S7 and S8 is in the negative, the processing moves to Step 10, and the disregard flag is set to 0. If the judgments in Steps S7 and S8 are both in the affirmative the disregard flag is set to 1 (Step S9)

Step S11 is a judgment as to whether the composition_state

of the newly read PCS is of the Normal Case type or of the Epoch Continue type. If the composition_state is of the Epoch Start type the disregard flag is set to 0 (Step 10).

0084

5 Step S11 is a judgment as to whether the composition_state of the newly read PCS is of the Normal Case type or of the Epoch Continue type. If the composition_state is of the Normal Case type Step S12 is executed as an additional check. Step 12 is for judging whether a graphics Object is present in the object buffer, and whether
10 a PCS, PDS and WDS are present in the composition buffer 16. If all of these are present, the disregard flag is set to 0 (Step 10). If any are lacking, the processing transfers to Step S9.

0085

If there is no graphics object present in the object buffer,
15 it may be that sufficient functional segments to form an interactive screen were not originally obtained.

FIG. 26 shows a manner in which Display Sets are read when the two AV clips shown in FIG. 14 are played back. Level 3 shows Display Sets multiplexed in an AV Clip, level 2 shows a plurality
20 of pictures that compose a video stream, and level 3 shows states of the graphics decoder.

0086

When DS1, which is positioned at the head of an Epoch, is read, the graphics decoder is reset, and the coded data buffer 13 reads
25 in order the PCS, WDS, PDS, and ODS that compose the DS1. The PCS, WDS and PDS are then transmitted to the composition buffer 16, and the ODS is outputted to the stream graphics processor.

The arrow mrl indicates a time at which DS_m is read. The coded

data buffer 13 reads in order the PCS, WDS, PDS, and ODS constituting the DSM. Since the connection_condition of the DSM is of the Acquisition Point type, the PCS, WDS and PDS are discarded without being transmitted to the composition buffer 16. Moreover, the ODS is discarded without
5 being transmitted to the Stream Graphics Processor.

0087

The arrow mr2 indicates a time at which DSM + 1 is read. Here, the graphics decoder judges whether or not the three conditions have been met. If a change stream of the DSM + 1 indicates Epoch Continue,
10 if playback of the video streams is seamless, and if a composition_number of DSM + 1 matches the composition_number of the PCS in the Composition Buffer, the three conditions are met, and the DSM + 1 is treated as an Acquisition Point. With this method, the reproduction device does not reset the graphics decoder, and
15 discards the PCS, WDS and PDS read from the coded data buffer 13 without transmitting them to the composition buffer 16. The reproduction devices similarly discards the ODS without outputting it to the Stream Graphics Processor.

0088

20 The above describes the processing involved in normal playback. In the case of skip playback of an AV Clip, which occurs as a result of skipping between chapters, a chapter search, or the like, the playback device instantaneously resets the graphics decoder upon receipt of the skip instruction. Consequently, a current
25 composition_number that is managed in the Graphics Decoder, will never match the composition_number of DSM + 1 in the AV Clip about to be played. Consequently, in the case of skip playback, the DSM + 1 is dealt with as an Epoch Start.

0089

FIG. 27 shows a method for reading to a graphics decoder when skip playback of the AV Clip #2 is carried out in order. Levels 1 to 3 are identical to those in FIG. 26, and the arrows have the same meaning as in FIG. 26. However, since the content of the graphic display in FIG. 27 differs from that of FIG. 26, the composition_number is different. When playback of the following AV Clip begins and the DS_m + 1 is read by the Coded Data Buffer 13, the graphics decoder interprets the PCS read by the Coded Data Buffer 13, and makes a judgment about the Change Stream. If the Change Stream is of the Epoch Continue type, the graphics decoder makes judgments about the remaining two conditions. Even if the playback of the video streams is to be seamless, the graphics decoder treats the DS_m + 1 as an Epoch Start type Display Set as a result of the composition_number being different from the preceding AV Clip. Consequently, the graphics decoder is reset, and the PCS, WDS and PDS read by the coded data buffer 13 is transmitted to the composition buffer 16, and the ODS is outputted to the stream graphics processor.

0090

20 *Second Embodiment*

The second embodiment relates to setting a PTS for realizing an Epoch Continue. When playing two AV Clips in order, it is necessary to take into account differences in the clocks used for reference by the respective AV Clips. At authoring, the AV Clips are encoded by different machines, and consequently generated based on differing clock signals. The clock used for reference at encoding is known as an STC (System Time Clock). The STC is also used as a reference for the decode processing when the reproduction device plays back

an AV Clip.

0091

To playback two AV Clips with differing STCs consecutively, the playback device calculates a and STC difference value (STC_delta), adds the STC_delta to an internal clock time so as to compensate for the differences in STCs. FIG. 28 for comparison shows a PTS value of a video stream belonging to the preceding AV Clip and a PTS value of a video stream belonging to the following AV Clip. In the case that A start time for last graphics display by the playback device during the preceding AV Clip is PTS(1stEND), the picture display period is Tpp, and a starting time at which the first picture of the following AV Clip is displayed is PTS(2ndSTART), the STC_Delta is expressed as

$$\text{STC_delta} = \text{PTS}(1\text{stEND}) + \text{TP} - \text{PTS}(2\text{ndSTART}).$$

STC_delta can be expressed in this way because when two AV clips are played back consecutively, the PTS(1stEND) + Tpp should match PTS(2ndSTART), and the difference between the PTS(1stEND) + Tpp and PTS(2ndSTART) can therefore considered to be the difference in the STCs.

0092

When the two AV Clips are to be played back contiguously, both the PTS(1stEND) and the PTS(2ndSTART) are detected and used to calculate STC_delta. The STC_delta is then added to the counter value of the clock inside the playback device, and the corrected counter value outputted to the video decoder 5, the audio decoder 7, and the graphics decoder 12. By making reference to the corrected counter value, the video decoder 5, the audio decoder 7, and the graphics decoder 12 are able to play back the video streams, the audio streams,

and the presentation graphics streams of the respective AV clips without a pause between the two streams.

0093

The value of a $PTS(DSm + 1[PCS])$ of $DSm + 1$ at the head of the graphics stream belonging to the following AV Clip is adjusted to ensure that the above-described processing proceeds smoothly. The nature of the adjustment is to have the $PTS1(END)+Tpp$ and $PTS(2ndSTART)$ indicate the same time. This adjustment is necessary for the following reasons. If the time lag before the first display in the following AV Clip is long, the graphics decoder may be reset. Since the AV Clips in the BD-ROM are each stored in separate files there is a time lag when reading two consecutive files. Consequently, if the reading of the AV Clips is for some reason further delayed, the risk of reset increases greatly. To deal with this problem, the Display Set of the Epoch Continue type at the head of the following AV Clip has the value of $PTS(DSm + 1[PCS])$ set to indicate an identical time to $PTS(1stEND)+Tpp$, so that display of the graphics takes place at a timing identical to display of the first picture of the video stream.

20 0094

Setting the value of $PTS(DSm + 1)$ in this way enables the time period between the last display of graphics in the preceding AV Clip and the first display in the following AV Clip to be minimized, even when there is a substantial time lag between completing the reading of the preceding AV Clip and starting the reading of the following AV Clip. Since the reproduction device is thereby prevented from resetting, the presence of management data already in the memory can be continuous.

0095

Third Embodiment

The first embodiment describes the PG stream. The third
5 embodiment, on the other hand, describes the IG stream. The following
describes the Interactive Graphics Stream. FIG. 29A shows a structure
of an Interactive Graphics Stream. Level 1 shows TS packets that
constitute the AV Clip. Level 2 shows the shows PES packets that
constitute the graphics stream. The PES packets in the level 2 are
10 constructed by extracting payloads from packets having a predetermined
PID and connecting the extracted payloads. Since the presentation
graphics stream is unrelated to the main point of the third embodiment,
the presentation graphics stream is not described below.

0096

15 The third level shows the construction of the Interactive
Graphics Stream. The Interactive Graphics Stream composed of
functional segments called ICSS (Interactive Composition Segments),
PDSs (Palette Definition Segments), ODSs (Object Definition Segments),
and ENDS (END of Display Set Segments). Of these functional segments,
20 the ICS is known as a screen composition segment, and the PDS, ODS
and END are known as definition segments. The PES packets may be
in one-to-one correspondence, or one-to-many correspondence with
the functional segments. In other words, each functional segment
is either converted to a single PES packet and recorded on a BD-ROM
25 or fragmented, converted into a plurality of packets and stored on
a BD-ROM. FIG. 29B shows the PES packets obtained by converting the
functional segments.

0097

The following describes the various functional segments. Interactive Composition Segments (ICS) are functional segments for controlling the screen composition of an Interactive Graphics Object. The ICS of the third embodiment is for realizing a multi-page menu.

5 The functional segments of various types have a logical structure such as the one shown in FIG. 30. FIG. 30 shows a logical structure made up of functional segments of various types. Level 1 in FIG. 30 shows an Epoch, level 2 shows a Display Sets, and level 3 shows a each of the various types of Display Set. The functional
10 segments shown in level 3 of FIG. 29A are shown in level 4 of FIG. 30. The IG stream also contains Epoch Start-type, Acquisition Point-type and Epoch Continue-type functional segments. However, the ICS differ from the PCSs in that the Acquisition Point-type functional segments allow for update on a page-by-page basis.

15 0098

The IG stream is characterized by control of behavior of the multi-pagemenu in accordance with progress, along the above-described playback time axis, of moving picture playback. The new composition that allows this characteristic to be realized relates to an
20 interactive_composition in the ICS. The following describes the internal structure of the interactive_composition.

FIG. 31A and FIG. 31B show the correspondence between the ICS and the interactive_composition. The relationship between the ICS and the interactive_composition is either a one-to-one correspondence
25 of the type shown in FIG. 7A or a one-to-many correspondence of the type shown in FIG. 31B.

0099

The relationship is a one-to-one correspondence when a data

size of the interactive_composition is small enough to be stored in a single ICS.

The relationship is a one-to-many correspondence when a data size of the interactive_composition is large, and the interactive_composition is fragmented and stored by a plurality of ICS. Since the interactive_composition can be stored using a plurality of ICS, there is no limit to its data size, which may be increased to, say, 512 kMB, 1 MB, or more. A one-to-many correspondence is also possible between the ICS and the interactive_composition. However, for simplicity, the case where the ICS and the interactive_composition are in one-to-one correspondence is used in the following description.

0100

FIG. 32 shows a data structure of an ICS. Each ICS stores either an entire interactive_composition or a portion of an interactive_composition obtained by fragmentation. As shown in the left hand side of FIG. 8, the ICS includes a segment_descriptor to indicate that it is an ICS, horizontal and vertical pixel numbers to be used by the ICS, a video_descriptor indicating a frame rate, a composition_descriptor, and an interactive_composition or a portion of an interactive_composition_data_fragment obtained by fragmentation.

0101

The arrow cul in FIG. 32 points to a close-up of a data structure of the composition_descriptor. As indicated, the composition_descriptor includes a composition_state field that indicates whether a Display Set to which the ICS belongs is of the Normal Case-type, the Acquisition Point-type, the Epoch Start-type, or Effect_Sequence-type, and a composition_number indicating a count

of screen combinations.

0102

The arrow cu2 of FIG. 32 points to a close-up of a data structure of the interactive_composition. As indicated, the interactive_composition includes an interactive_composition_length field, a stream_model field, a user_interface_model field, a composition_time_out_pts, a user_time_out_duration, and pieces of page information (1)(2)...(i)...(number_of_page-1), each of which corresponds to a displayable page in the multi-page menu.

10 0103

The interactive_composition_length field indicates the data length of the interactive_composition.

The stream_model field indicates a type of stream model the interactive_composition is using. The stream model indicates the format used to record the interactive_composition on the BD-ROM, and the manner in which the interactive_composition is to be managed by the composition buffer in the reproduction device. Specifically, the stream model indicates whether the graphics stream i) has been de-multiplexed from an AV Clip and loaded in the composition buffer or ii) has been preloaded in the composition buffer as a SubClip.

20 0104

The user_interface_model field indicates whether the user type of user interface assumed by the interactive_composition is an Always-onU/I or a Pop-upU/I. With an Always-onU/I a menu display/deletion occurs in accordance with playback progress of the AV Clip. With a Pop-upU/I, a menu display/deletion is triggered by a user operation.

0105

The composition_time_out_pts indicates an end period (Epoch
END) of the Epoch to which the ICS belongs. Since interactive control
by means of the ICS becomes impossible at the end period, the time
point indicated by the composition_time_out_pts indicates the end
5 of interactive control.

The selection_time_out_pts indicates a time period allowed
for a button in a selected state to automatically activate. More
specifically, each button corresponds to an item selection on the
multi-page menu, and the selection_time_out_pts stipulates the time
10 taken to alter the button to an active state upon selection.

0106

The IF statement in FIG. 32 (if(Stream_model=='0b')) shows
that the above-described composition_time_out_pts and
selection_time_out_pts are information elements that appear only
15 when the stream_model field = multiplexed. If the stream model is
preloaded, neither the composition_time_out field nor the
selection_time_out field are used

The user_time_out_duration field indicates a period of time
allowed before deletion for a page displayed in response to a user
20 operation. In the case of the Always-onU/I, since only pages from
the second page onwards are displayed in response to user operations,
only these SubPages are deleted when the user_time_out duration has
elapsed. After the SubPages are deleted, the first page is displayed.
In the case of the Pop-upU/I, on the other hand, since the every
25 page of the multi-page menu is displayed in response to a user operation,
all pages are deleted when the user_time_out_duration has elapsed.
The result is a state in which nothing is displayed (No Menu Display).

0107

FIG. 33 shows a data structure of page information for a given page (page y) among a plurality of pages in an x-th Display Set. As indicated to the right-hand side of FIG. 33, the page information (y) includes

- 5 i) a page_id that uniquely identifies page(y)
- ii) the content of the data structure conveyed by the page information (y), including a UO_mask_table field, an in_effect field, an out_effect field, an animation_frame_rate_code field, a default_selected_button_id_ref field, an animation_frame_rate_code field, a default_selected_button_id_ref field, a default_activated_button_id_ref field, a pallete_id_ref field, and button information (0)(1)...(number of buttons-1), and
- iii) a page_version_number indicating a version number of the content of the page information (y).

15 The following describes the various fields that constitute the data structure conveyed by the page information (y).

0108

The UO_mask_table field is a table used to permit/disallow user operations relating to the page(y).

20 The in_effect field indicates a display effect that is to be reproduced at first display of the page(y). The out_effect indicates a display effect to be reproduced upon display completion.

The animation_frame_rate_code field describes a frame rate that is to be applied when displaying animation in page(y).

25 0109

The default_selected_button_id_ref field indicates whether buttons whose default state is the selected state are determined dynamically or passively. Specifically, when the field contains 0xff,

the buttons whose default state is the selected state are determined dynamically. In this case, settings values in the Player Status Register (PSR) in the reproduction device are preferentially interpreted, and the buttons indicated in the PSR are set to the selected state. When the field does not contain 0xff, the buttons whose default state is the selected state are determined statically. In this case, the button numbers stipulated in the default_selecte_button_id_ref field are written over the PSR, and the corresponding buttons are set to the selected state.

10 0110

The default_activated_button_id_ref field indicates buttons automatically set in the active state when a time point indicated by the selection_time_out_pts is reached.

15 If the default_activated_button_id_ref field contains FF, the button in the selected state for the predetermined period is automatically selected. If the default_activated_button_id_ref field contains 00, the button in the selected state is not automatically selected. When the default_activated_button_id_ref field contains a value other than 00 or FF, the value is interpreted as an effective
20 button number

 0111

The pallete_id_ref field indicates the id of the palette to be set in the CLUT unit for the page(y).

25 The button information (button_info field) defines each button displayed on the page(y). The above-described fields specify the contents of each page in the multi-page menu.

The page_version_number field indicates a version of the content conveyed by the page information (y) in an Epoch. Since the

page_version_number field is a main feature of the current present invention, a detailed description is provided below. The version of page information (y) indicates a number of updates implemented on the content of the data structure conveyed by the page information.

- 5 The data structure of page information (y) is said to have been updated if there are one more changes in the values contained in the fields after the page_version_number field.

0112

The version indicated by the page_version_number field is
10 expressed using a serial number in a single Epoch. As a result, the value contained in the page_version_number field varies according to the Display Set that holds the page information in the Epoch. During the Epoch, the page_version_number field in the page information belonging to the Epoch Start Display Set is set to an
15 initial value (= 0). From the second Display Set in the Epoch onwards, the page_version_number fields belonging to the Display Sets that permit updates (i.e. Acquisition Point-type and Normal Case-type Display Sets) are each set to a value indicating a number of updates.

0113

20 The following describes the page_version_number in detail with reference to a specific example shown in FIG. 34. FIG. 34 shows settings for the page_version_number field in two consecutive Display Sets (DSx + 1, DSx). DSx + 1 is an Acquisition Point-type Display Set, and FIG. 34 shows arbitrary page information (y) in this Display
25 Set. When the content of the page information (y) of DSx + 1 is identical to that of DSx, the page_version_number field of the page information (y) in DSx + 1 is set to the same value as the page_version_number fields in the page information (y) in DSx. By referring to these

page_version_number fields, the reproduction device is able to judge that the content of page information (y) has not altered between the DSx and the DSx + 1. Contrastingly, in FIG. 35 the content of the page information (y) in the DSx + 1 differs to that in the page information (y) of the DSx. In this case, the value (= A + 1) contained in the page_version_number field of the DSx + 1 is incremented by one from that contained in the page information (y) of the DSx. The reproduction device is therefore able to discover whether the page information (y) in the DSx + 1 has altered from the page information (y) in the DSx.

0114

FIG. 36 shows a page composed of page information (y) in the DSx and Page information (y) in the DSx + 1 for comparison.

The page constituted by the page information (y) in the DSx + 1 has three buttons (A,B and C) disposed in an order: B, C, A.

On the other hand, the page constituted by the page information (y) in the DSx + 1 has the three buttons (A,B and C) disposed in an order: A, B, C. The only difference between the two pages is that the order of appearance of the buttons, which alters from A,B, C to B, C, A. Even in the case of such small variations, however, the value contained in the page_version_number field in the page information (y) of the DSx + 1 will increment. By setting the page_version_number field in this way, it is possible to signal to the reproduction device the existence of small changes in the page information (y).

0115

The above description gives an example of an Acquisition Point-type Display Set in the interactive_composition. Note, however,

that there is a page_version_number field in each piece of page information in the Normal Case-type Display Sets in the interactive_composition. Moreover, the page_version_number field can be made to indicate that content has altered between pages.

5 As in the first embodiment, when a preceding AV Clip and a following AV Clip satisfy the three conditions, the Epoch Continue-type Display Set can be treated as an Acquisition Point-type Display Set. Moreover, in the Acquisition Point-type Display Set it is possible to increment the page_version_number in each piece
10 of page information. Thus, among the pieces of page information in the ICS, which is stored in the composition buffer 16 and to which the Epoch Continue-type Display Set belongs, it is possible to limit updating to those pieces of page information whose page_version_number fields have increased.

15 0116

 The above description relates to an improvement over the prior art in the recording medium of the third embodiment. The following describes the reproduction device of the third embodiment. Since the above-described IG stream is constituted in the same way as the
20 PG stream, playback to the IG stream can be performed using the reproduction device having the internal structure shown in FIG. 24.

 The Epoch Continue-type Display Set exists in the IG stream, and the graphics controller 17 of the third embodiment therefore performs processing in accordance with the flow chart of FIG. 37.
25 This flow chart is the flow chart of FIG. 25 but with the letters ICS substituted for the letters PCS. Besides this substitution, the flow chart of FIG. 37 has additional steps of Step S21 and Step S22. Step S21 is executed in the case that the judgments of both Step

S7 and Step S8 are both affirmative and segmentK is to be treated as an acquisition point. In Step S21, the reproduction device judges whether or not page information having an altered page_version_number exists, and if judging in the affirmative, exchanges the corresponding
5 page in the interactive_composition in the composition buffer 16 for a new page. It is thereby possible to update each piece of page information in the Epoch Continue-type Display Sets.

0117

According to the third embodiment described above, Epoch
10 Continue-type Display Sets are present among the Display Sets used to realize the display of menus, and it is therefore possible to perform consecutive playback of two AV Clips without breaks occurring.

Fourth Embodiment

15 The fourth embodiment relates the manufacturing process of the BD-ROM. FIG. 38 is a flow chart showing the manufacturing process for producing the BD-ROM described in the first to third embodiments.

0118

The BD-ROM manufacturing process includes a material
20 production process S201 in which material is produced by methods such as recording moving pictures and sound, an authoring process S202 in which the material is formatted to an application format using an authoring machine, and a pressing process S203 to complete the BD-ROM through production of a master disk and pressing/sticking.

25 The authoring process for the target BD-ROM further includes the Steps S204 to S213, which are described below.

0119

The following describes Steps S204 to S213. In Step S204 control

information, palette definition information, and graphics are described. In Step S205, the control information, the palette information, and the graphics are converted to functional segments. In Step S206, the ICS and PTS are set based on a playback timing of a picture that is to be synchronous. In Step S207, DTS[ODS] and PTS[ODS] are set based on a value of PTS[ICS]. In Step S208 DTS[ICS] and PTS[PDS] are set based on a value of DTS[ODS].

0120

In Step S209 occupancy of each of the buffers in the player is plotted against time. In Step S210, it is judged whether or not the plotted transitions stay within constraints of the player model. If the judgment is in the negative, each functional segment is overwritten in Step S211. If the judgment is in the affirmative, a Graphics Stream is generated in Step S212, and the graphics stream is multiplexed with a video stream and an audio stream to form an AV Clip in Step S213. The AV Clip is then adapted to the BD-ROM format to complete the application format.

0121

Modifications

Though the present present invention has been described by way of the above embodiments, the present present invention is not limited to such. The present present invention can be realized with any of the modifications (A) to (L) below. The present invention of the claims of this application includes extension and generalization of the above embodiments and their modifications below. The degree of extension and generalization included is based on the state of the art in the technical field of the present invention at time of application.

0122

(A) The above embodiments relate to the case where BD-ROM is used as the recording medium. The main features of the present invention, however, are to be found in the Graphics Stream recorded on the recording medium and are not dependent on the physical characteristics of BD-ROMs. Therefore, the present invention is applicable to any recording medium able to record a graphics stream. Examples of such a recording medium include: an optical disk such as a DVD-ROM, a DVD-RAM, a DVD-RAM, a DVD-RW, a DVD-R, a DVD+RW, a DVD+R, a CR-R or a CD-RW; a magneto-optical disk such as a PD or an MO; a semiconductor memory card such as a CompactFlash card, a SmartMedia card, a Memory Stick card, a MultiMediaCard, or a PCM-CIA card; a magnetic disk such as a flexible disk, SuperDisk, Zip or Klik!; a removable hard disk drive such as ORB, Jaz, SparQ, SyJet, EZFley, or Microdrive; a nonremovable hard disk drive.

0123

(B) The above embodiments describe the case where the reproduction device decodes an AV Clip recorded on the BD-ROM and output the decoded AV Clip to the television. As an alternative, the reproduction device may only have a BD drive with the remaining construction elements being provided in the television. In this case, the reproduction device and the television can be incorporated into a home network using an IEEE 1394 connector. Moreover, though the above embodiments describe the case where the reproduction device is connected to the television, the reproduction device may instead be integrated with a display device. Also, the reproduction device of any of the embodiments may contain only the system LSI (integrated circuit) that performs essential processing. The above described

reproduction devices and integrated circuits are all within the scope of the present invention described in this specification. Thus any act of manufacturing a reproduction device based on the internal construction of the reproduction device described in the embodiments
5 is an act of implementing the present invention. Moreover, any act of assigning a charge (i.e. selling), giving , leasing, and/or importing the reproduction device is an act of implementing the present invention.

0124

10 Since information processing using the programs shown in the flowcharts realized using hardware resources, the programs describing the operation procedures shown in the flow charts by themselves constitute an present invention. The above embodiments describe the case where the programs are incorporated with in the reproduction
15 apparatus, but the programs can be implemented separately from the reproduction device as described in the first embodiment. Acts of implementing the programs include (1) an act of producing, (2) an act of assigning with or without charge, (3) an act of leasing, (4) an act of importing, (5) an act of providing to the public via a
20 bi-directional electronic communications network, and (6) an act of offering for assignment or lease for storefront displays, catalogs, or brochures.

0125

Executed in series, the steps in the flow charts can be regarded
25 as the necessary elements of the present present invention. Thus, the procedure shown by these flow charts discloses a form of use of the playback method. If the processing of the steps shown in any of the flow-charts is performed in sequence so as to achieve the

intended aim and intended effect of the present invention, this clearly constitutes an implementation of the recording method of the present invention.

0126

5 (E) When used in a home network interconnected via IEEE 1394, the reproduction device may transmit an Aligned Unit using the following processing. The reproduction device removes a TP_extra_header from each of the 32 EX TS packets in the aligned unit encrypts the body of each TS packet according to the DTCP
10 Specification, and outputs the encrypted TS packets. When outputting the TS packets, the reproduction device inserts an isochronous packet between adjacent TS packets. The insertion position determined based on a time indicated by an arrival_time_stamp in TP_extra_header. The reproduction device outputs a DCTP_descriptor together with the
15 output packets. The DCTP_descriptor corresponds to a copy permission indicator in the TP_extra_header. When the reproduction device is used in a home network interconnected via IEEE 1394 and the DCTP_descriptor indicates "copying prohibited", the TS cannot be recorded to other devices.

20 (F) The digital streams of the above embodiments are AV Clips in the Blu-ray Disk Read-Only Format, but the present invention can also be realized using a VOB (Video Object) of the DVD-video Format, or the DVD-Video Recording Format. The VOB is a recording stream that complies with the ISO/IEC 13818-1 Standard and is obtained
25 by multiplexing a video stream and an audio stream. Also, the video stream in the AV Clip may be an MPEG 4 video stream or a WMV video stream. Further, the audio stream in the AV Clip may be a Linear PCM audio stream, a Dolby AC-3 audio stream, an MP3 audio stream,

an MPEG-AAC audio stream, or a dts audio stream.

0127

(G) The movie described in the above embodiments may be obtained by encoding an analog image signal that has been broadcast using analog broadcasting techniques. Alternatively, the movie may be stream data made up of a transport stream that has been broadcast using digital broadcasting techniques.

An analog/digital image signal recorded on videotape may be encoded to obtain content. An analog/digital image signal directly captured by a video camera may be encoded to obtain content. Another possibility is that the content is a digital work distributed by a distribution server.

0128

(H) The Graphics Objects described in the above embodiments is run-length encoded raster data. The reason that run-length encoding is used to compress/encode Graphics Objects is that run-length encoding is suitable for the compression and decompression of subtitles. One of the properties of subtitles is that a relatively large number of pixels having the same pixel value are aligned in the horizontal direction. Due to this property, it is possible to obtain a high compression ratio when compression is carried out using run length encoding. Moreover, since the decompression load is light, and the processing to decode the compressed data is suitable for a software implementation. In the device used to realize the decoding, the same compression/decompression method is used for the Graphics Object as for the subtitles. Note however, that the use of run length encoding on the Graphics Object is not essential to the present invention. For instance, the Graphics Objects may be PNG data, vector

data or transparent parents.

0129

(I) The transmission rate R_c may be set so that clearing of the graphics plane and rendering are completed within a vertical blanking time. If the vertical blanking time is set to 25% of $1/29.93$ seconds, the R_c will be 1Gps. This way of setting R_c enables graphics to be displayed smoothly, and is very effective in practice.

In addition to taking place within the vertical blanking time, the writing can be synchronized with a line scan. This enables the subtitles to be displayed smoothly with $R_c = 256$ Mps

0130

(J) The reproduction device in the above embodiments includes a graphics plane. However, a line buffer that stores the uncompressed pixels of one line may be used in place of the graphics plane. Conversion to an image signal is possible using the line the buffer since such conversions are performed one line at a time.

(K) The graphics plane in the above embodiments is preferably made up of a double buffer. In the case that graphics plane is made up of a double buffer, it is possible to switch between screens instantaneously, even when graphics having a large data size are written to the graphics plane over a period of a number of frames. The inclusion or lack of the double buffer is therefore significant if full screen menus are to be displayed.

0131

Three conditions are described for a Display Set ($DS_m + 1$) to be treated as an Acquisition Point. First, the Display Set ($DS_m + 1$), which directly follows the AV Clip boundary; must be of the Epoch Continue-type (Condition 1). Second, the composition_number

contained in the PCS belonging to the DSm + 1 must be identical to the composition_number contained in a directly preceding Display Set DSm (Condition 2). Third, playback of the preceding AV Clip and playback of the following AV Clip must be seamlessly connected. However, the second and third of these conditions are not necessary conditions. Provided that the first condition is satisfied (i.e. the Display Set (DSm + 1) that immediately follows the AV Clip boundary is of the Epoch Continue type), the Display Set DSm + 1 can be treated as an Acquisition Point.

10 0132

Industrial Applicability

The recording medium and reproduction device of the present invention can be used as part of a home theater system or the like. However since the above embodiments disclose internal constructions of recording medium and reproduction device of the present invention, and the mass production is possible based on the disclosed internal constructions, the recording medium and the reproduction device are of industrial use. In other words, the recording medium and the reproduction device have industrial applicability.

20